

Cerniera per porte "Rapida"

Cerniera registrabile a due ali in alluminio. La registrazione avviene senza dover sfilare l'anta, mediante la rotazione delle due boccole eccentriche sulle quali è stata creata una sede esagonale con inserto di rinforzo in acciaio inox. Il sistema di sicurezza antieffrazione è posto sul perno per mezzo di un anello antisfilamento. Portata di 2 cerniere Kg. 90.

DOTAZIONI

2 riscontri in alluminio per il fissaggio
1 perno antisfilamento mm 11
in acciaio inox

2 boccole registrabili in bisolfuro
di molibdeno
4 viti TCEI 6MA x 14 inox



Hinge for "RAPIDA" doors

Adjustable two-wing hinge, made from steel. You can adjust it without having to dismantle the hinge, by rotating the two eccentric bushes on which a hexagonal housing has been created with a stainless steel support insertion. The break-in security system is positioned on the pin (using a slip-proof ring).

Capacity of 2 hinges, Kg 90.

SUPPLIED PARTS

2 aluminum securing check plates
1 stainless steel slip-proof pin 11 mm
2 adjustable molybdenum bisulphate
bushes

4 stainless steel TCEI 6MA x 14 screws
2 stainless steel 6MA x 10 grub screws
2 nylon stoppers

art.08300.00.00



- scatola da 8 pezzi / box of 8 units

