

Cerniera per porte "Rapida" 3 ali

Cerniera registrabile a tre ali in alluminio. La registrazione avviene senza dover sfilare l'anta sia mediante la rotazione delle due boccole eccentriche alle due estremità, sia sulla boccola centrale, in questo caso mediante apposito chiavino ns. art. 06890.00.00. Il sistema di sicurezza antieffrazione è posto sul perno per mezzo di un anello antisfilamento.

Portata di 2 cerniere Kg 100



DOTAZIONI

3 riscontri in alluminio per il fissaggio
1 perno antisfilamento mm 11 in acciaio inox
3 boccole registrabili in bisolfuro di molibdeno

6 viti TCEI 6MA x 14 inox
3 grani 6MA x 10 inox
2 tappi in nylon
1 grano 5MA x 5 inox

Hinge for 3-wing "RAPIDA" doors

Adjustable two-wing hinge, made from steel. You can adjust it without having to dismantle the hinge, by rotating the two eccentric bushes on which a hexagonal housing has been created with a stainless steel support insertion. The break-in security system is positioned on the pin (using a slip-proof ring).

Capacity of 2 hinges, Kg 100.

SUPPLIED PARTS

3 aluminum securing check plates
1 stainless steel slip-proof pin 11 mm
3 adjustable molybdenum bisulphate bushes
6 stainless steel TCEI 6MA x 14 screws

3 stainless steel 6MA x 10 grub screws
2 nylon stoppers
1 stainless steel 5MA x 5 grub screw

art. 08310.00.00



- scatola da 8 pezzi / box of 8 units

